

WET RUBBING FASTNESS IMPROVER JV-318

I.MAIN COMPONENTS

Silicone modified special polymer copolymer.

II. TECHNICAL INDICATORS

Appearance: milky white viscous flow body

Ionic: nonionic

PH value: 6-7

Soluble in water

Safety: non toxic, no irritating smell

III. CHARACTERISTICS AND PERFORMANCE

This product belongs to environmental protection products;

The wet rubbing fastness of the treated fabrics can be improved by 1-2 grades;

It doesn't affect the color and luster, and it feels soft after finishing;

Strong stability, acid and alkali salt resistance, hard water resistance;

No demulsification, no stick stick, easy to operate and use;

It can solve the problem of various functional auxiliaries in the same bath. It can be used with fixing agent and silicone oil in the same bath, and can be upgraded to 0.5-1 level;

IV. SCOPE OF APPLICATION

It is suitable for solid color treatment of cellulose fiber activity, direct, vulcanization, Shilin and other dyes to improve dry and wet friction fastness after dyeing.

V. METHODOLOGY OF USE

1. Spraying process: after 25% thinning, spray the fabric with spray gun, and then dry it. (after diluting, filter it with 100-200 mesh filter cloth and load it into the spray gun to prevent blocking the spray gun pipe.)

2. Soaking process: (mainly used for knitted fabrics)

Jv-318: dosage 1.0-2.0% (o.w.f) bath ratio: 1:15-20

Technological process: dip jv-318 into dyed fabric and dry it at 50 ℃ for 30min (105 ℃)

Soaking, rolling and drying at 20-50g.

*This product can be bath with fixing agent, silicone oil and soft oil, but pioneer experiment is needed.

The best technological formula has been obtained*

VI. STORAGE AND PACKAGING

It is packed in 125kg plastic barrel and stored at normal temperature. Please cover the container tightly when not in use. Generally, it can be stored for more than 6 months.

东莞市洁威实业有限公司 DONGGUAN JERVAY INDUSTRIAL CO.,LTD.

Web:www.jervay.com Contact person:Mr.Finn Email:jv@jervay.com Tel:+86 150 1475 1722

The above information and data are for reference only. Customers should do laboratory samples in advance to determine the specific process and dosage. The company only to product specifications, quality consistency to guarantee. Customers due to the addition of other additives, or due to process and fabric losses, the company is not responsible.